

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/936551INTERNATIONAL APPLICATION NO.
PCT/GB00/00994INTERNATIONAL FILING DATE
March 17, 2000PRIORITY DATE CLAIMED
March 19, 1999TITLE OF INVENTION **STRAIN SENSING**APPLICANT(S) FOR DO/EO/US **Christopher GROVES-KIRKBY, Ian BENNION; John WILLIAMS, Lin ZHANG**

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371 (f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☐ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
 - a. ☐ is attached hereto.
 - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11 to 20 below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
14. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☒ Other items or information: **Receipt Acknowledgment Postcard**

U.S. APPLICATION NO. (if known, see 37 CFR 1.53)

09/936551

INTERNATIONAL APPLICATION NO
PCT/GB00/00994

ATTORNEY'S DOCKET NUMBER
P/61761-PCT

21. ☒ The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :

Neither international preliminary examination fee (37 CFR 1.482)
nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO
and International Search Report not prepared by the EPO or JPO \$1,000.00

International preliminary examination fee (37 CFR 1.482) not paid to
USPTO but International Search Report prepared by the EPO or JPO \$860.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO
but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$710.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO
but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$690.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO
and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

CALCULATIONS PTO USE ONLY

\$860.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492 (e)).

\$0.00

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$
Total claims	19 - 20 =	0	x \$18.00	\$0.00
Independent claims	3 - 3 =	0	x \$80.00	\$0.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$270.00	\$0.00
TOTAL OF ABOVE CALCULATIONS =				\$860.00
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				\$0.00
SUBTOTAL =				\$860.00
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$0.00
TOTAL NATIONAL FEE =				\$860.00
Fee for recording the enclosed assignment (37 CFR 1.21 (h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				\$0.00
TOTAL FEES ENCLOSED =				\$860.00
				Amount to be refunded: \$
				charged: \$

\$

Total claims 19 - 20 = 0 x \$18.00 \$0.00

Independent claims 3 - 3 = 0 x \$80.00 \$0.00

MULTIPLE DEPENDENT CLAIM(S) (if applicable) + \$270.00 \$0.00

TOTAL OF ABOVE CALCULATIONS = \$860.00

☐ Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above
are reduced by 1/2. \$0.00

SUBTOTAL = \$860.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(f)). \$0.00

TOTAL NATIONAL FEE = \$860.00

Fee for recording the enclosed assignment (37 CFR 1.21 (h)). The assignment must be
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property + \$0.00

TOTAL FEES ENCLOSED = \$860.00

Amount to be
refunded: \$

charged: \$

a. ☒ A check in the amount of **\$860.00** to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. 11-1145 in the amount of \$_____ to cover the above fees.
A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any
overpayment to Deposit Account No. 11-1145. A duplicate copy of this sheet is enclosed.

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail No.
EL 337 911 326 US in an envelope addressed to: Commissioner of Patents and Trademarks, Washington, D.C. 20231, on:
September 14, 2001
(date)

Alan Israel Reg. No. 27,564

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Alan ISRAEL, Esq.
KIRSCHSTEIN, OTTINGER, ISRAEL & SCHIFFMILLER, P.C.
489 Fifth Avenue
New York, New York 10017
212/697-3750


SIGNATURE: 

Alan Israel
NAME

27,564
REGISTRATION NUMBER

Docket No.: P/61761

PATENTS
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

I hereby certify that this correspondence is being deposited with the U.S. Postal Service as Express Mail No. EL 327 911 326 US in an envelope addressed to: Box: PCT, Commissioner of Patents and Trademarks, Washington, D.C., 20231, on:
September 14, 2001
(date) 
Alan Irtzel
Reg. No. 27,564

International Application No.: PCT/GB00/00994
International Filing Date : March 17, 2000
In re: Application of : Christopher GROVES-KIRKBY, et al.
Deposited : September 14, 2001
For : STRAIN SENSING

New York, New York
September 14, 2001

PRELIMINARY AMENDMENT

BOX: PCT
Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Prior to calculation of the filing fee and before examination, kindly amend the above captioned application as follows:

IN THE CLAIMS:

Please cancel claims 1-19, without prejudice.

Please add the new set of claims set forth on the enclosed pages.

IN THE ABSTRACT:

Delete the "Abstract" on the PCT cover sheet and replace it with the "Abstract of the Disclosure" set forth on a separate sheet attached hereto.

REMARKS

An abstract has been provided on a separate sheet; and the claims have been amended to conform to U.S. practice.

Wherefore, an early action on the merits is earnestly solicited.

Respectfully submitted,

KIRSCHSTEIN, OTTINGER, ISRAEL & SCHIFFMILLER, P.C.


Attorneys for Applicant(s)

489 Fifth Avenue

New York, New York 10017-6105

Tel: (212) 697-3750

Fax: (212) 949-1690



Alan Israel

Registration No. 27,564

PROPOSED NEW CLAIMS

20. A strain sensor, comprising: an optical waveguide having a plurality of reflecting structures spaced lengthwise along the waveguide, each reflecting structure having a reflectivity for reflecting light at a different characteristic wavelength which changes in dependence upon a change of physical length of at least part of the respective reflecting structure, the reflectivity of reflecting structures which reflect at characteristic wavelengths which are adjacent to each other being different for discriminating between adjacent reflecting structures.

21. The strain sensor according to claim 20, in which the reflecting structures which reflect at adjacent wavelengths are configured such that one of the reflecting structures reflects the light at one characteristic wavelength, and the reflecting structure adjacent in wavelength is configured to reflect the light at two characteristic wavelengths.

22. The strain sensor according to claim 21, in which the reflecting structure which reflects the light at two wavelengths is configured such that the two characteristic wavelengths are separated by at least a width of the reflectivity of the reflecting structure which reflects at the adjacent wavelength.

23. The strain sensor according to claim 20, in which the optical waveguide comprises an optical fiber.

24. The strain sensor according to claim 20, in which each reflecting structure comprises a grating structure having a pitch, and wherein a change in the characteristic wavelength is in consequence of a change in the pitch of the grating structure.

25. The strain sensor according to claim 24, in which each grating structure comprises a Bragg grating.

26. The strain sensor according to claim 24, in which the optical waveguide is an optical fiber that includes a photo-refractive dopant, and in which each grating structure is optically written into the optical fiber.

27. The strain sensor according to claim 26, in which the optical fiber comprises silica doped with germanium oxide.

28. An apparatus for measuring strain, comprising: a strain sensor including an optical waveguide having a plurality of reflecting structures spaced lengthwise along the waveguide, each reflecting structure having a reflectivity for reflecting light at a different characteristic wavelength which changes in dependence upon a change of physical length of at least part of the respective reflecting structure, the reflectivity of reflecting structures which reflect at characteristic wavelengths which are adjacent to each other being different for discriminating between adjacent reflecting structures; a light source operable for applying the light to the waveguide, the light having a wavelength range which covers at least a range of wavelengths over which the reflecting structures reflect; and detector means for determining a change of characteristic wavelength at which the reflecting structures reflect light, the change being indicative of a change in length of at least a part of the respective reflecting structure.

29. The apparatus according to claim 28, in which the detector means determines the change in characteristic wavelength by measuring the wavelengths at which the strain sensor reflects the light.

30. The apparatus according to claim 28, in which the detector means measures the light transmitted by the strain sensor and determines the change of characteristic wavelength by measuring the change in wavelength at which light transmission is attenuated.

31. The apparatus according to claim 28, in which the detector means further comprises means for utilizing a relative magnitude of an intensity of reflected light or a relative magnitude of an intensity at which light transmission is attenuated to discriminate between the reflecting structures which are adjacent in wavelength.

32. A method of measuring strain, comprising the steps of: providing a strain sensor including an optical waveguide having a plurality of reflecting structures spaced lengthwise along the waveguide, each reflecting structure having a reflectivity for reflecting light at a different characteristic wavelength which changes in dependence upon a change of physical length of at least part of the respective reflecting structure, the reflectivity of reflecting structures which reflect at characteristic wavelengths which are adjacent to each other being different for discriminating between adjacent reflecting structures; applying the light to the waveguide, the light having a wavelength range which covers at least a range of wavelengths over which the reflecting structures reflect the light; and detecting a change in the characteristic wavelength at which the reflecting structures reflect the light.

33. The method according to claim 32, and further comprising the step of detecting the change in the characteristic wavelength by measuring the wavelengths at which the strain sensor reflects the light.

34. The method according to claim 33, and further comprising the step of detecting the change in the characteristic wavelength by measuring the wavelengths at which the transmission of the light through the strain sensor is attenuated.

35. The method according to claim 34, and further comprising the step of detecting a relative magnitude of an intensity of reflected light or a relative magnitude of an intensity

at which transmitted light is attenuated to discriminate between the reflecting structures which are adjacent in wavelength.

36. The method according to claim 32, and further comprising the step of sweeping the wavelength of the light applied to the strain sensor.

37. The method according to claim 32, in which, when it is desired to measure the strain within an object, further comprises the step of securing a part of the waveguide having at least a part of one of the reflecting structures to the object such that a change in a physical length of at least a part of the object causes a change in a physical length of at least the part of the one reflecting structure.

38. The method according to claim 32, in which, when it is desired to measure a temperature of an object, further comprises the step of placing a part of the waveguide having at least a part of one of the reflecting structures in thermal contact with the object such that a change in the temperature of the object causes a change in a physical length of at least the part of the one reflecting structure.

STRAIN SENSING

This invention relates to strain sensing and more especially to a strain sensor, apparatus for use with and a method of operating a strain sensor for sensing structural health and load monitoring.

5 Structural health and load monitoring of structures such as bridges and buildings is well known. Typically such systems measure the tensile or compressive strain within the structure, that is the change of length (extension or contraction) relative to the original length, which is indicative of the loading of the structure. Such information can be used in assessing damage and warning of impending weakness in the structural integrity of
10 structures such as aircraft, space platforms, marine vessels, bridges and other structures as well as in their engineering design.

To measure strain within such structures it is known to use a strain sensor. Early strain sensors relied on a change in electrical resistance with strain and typically comprised four
15 terminal devices in which two terminals were used to apply electrical current to the device and the other two for accurately sensing the potential difference developed across it. A particular disadvantage of such electrical resistance sensors is that when it is required to measure strain at a large number of points, as would be the case in structural monitoring of structures such as bridges and buildings, such sensors require a very large
20 number of electrical connections, making them cumbersome and prone to electrical failure.

More recently optical fibre strain sensors have been proposed which overcome a number of the problems of electrical resistance sensors. Optical fibre strain sensors comprise an optical fibre containing a number of components which are responsive to applied strain. Such components can comprise birefringent elements, micro-bends, Fabry-Perot resonators or intra-core Bragg gratings. In the case of the latter which are often termed fibre Bragg gratings, each Bragg grating which itself constitutes a respective strain sensor, reflects light at a characteristic wavelength which is determined by the pitch of the grating. This characteristic wavelength will change if the optical fibre is subjected to tensile or compressional strain which affects the pitch of the grating. Strain is measured by measuring a change in the characteristic wavelength of each grating. By providing a number of gratings along the length of the fibre, each of which reflects light at a different characteristic wavelength, it is possible to measure strain at a number of different points along the optical fibre.

Optical fibre strain sensors offer a number of advantages compared to electrical strain sensing techniques, making them attractive for structural health monitoring applications. For example, the Bragg grating characteristic wavelength is a linear function of change in grating pitch; fibre Bragg gratings are inherently wavelength encoded and consequently problems of intensity magnitude variation are eliminated, being fully integrated within the optical fibre eliminates any point of mechanical weakness, they are immune to electro-magnetic interference (EMI), are lightweight, resistant to corrosion and fatigue, inherently safe in that they cannot initiate fires or explosions and are compatible with fibre reinforced materials. In relation to the latter their compatibility has lead to the emergence of so-called "smart structures" which structurally integrate optical fibre

sensors thereby enabling continual monitoring of the internal strain of the structure and/or any load to which it is subjected.

Whilst optical fibre strain sensing is found to be effective the inventors have appreciated
5 that it suffers from certain limitations. Fibre Bragg gratings can be addressed in the wavelength, time and space domains. The number of fibre Bragg grating sensors that can be integrated into a single fibre and addressed by wavelength multiplexing is limited which is a consequence of the limited spectral range of the optical sources which are used to operate such sensor systems. Typically, the spectral range of the currently available
10 optical sources is 30 to 40 nm and it is usually required to be able to measure strains in the region of 3,000 to 5000 $\mu\epsilon$ (that is a 0.3% - 0.5% mechanical extension/contraction) which corresponds to a change in the characteristic wavelength of between 3 to 5 nm. In order to effectively operate a number of Bragg grating sensors within a single optical fibre it is necessary to dedicate a well defined wavelength range to each sensor to ensure
15 that at its maximum wavelength change the characteristic wavelength of any given sensor cannot intrude upon the wavelength range of the sensor in the adjacent wavelength band since, under these conditions, it is impossible to discriminate between light reflected from the two sensors. As a result the number of gratings that can be incorporated in a single fibre is limited.

20

The present invention has arisen in an endeavour to overcome at least in part the limitations of the known strain sensing arrangements.

According to the present invention a strain sensor comprises an optical waveguide having

a plurality of reflecting structures along its length, wherein each structure reflects light at a different characteristic wavelength which changes in dependence on a change of physical length of at least part of the reflecting structure; characterised in that the reflectivity of reflecting structures which reflect at characteristic wavelengths which are adjacent to each other are configured to be different such that the intensity of light reflected from adjacent structures can be used to discriminate between them. Since discrimination between the reflection characteristics of structures which are adjacent in wavelength is based on the relative magnitude of their reflectivities, this allows reflecting structures to have overlapping wavelength bands thereby enabling more reflecting structures to be incorporated within an optical waveguide for a given optical spectral range.

By securing the regions of the optical waveguide which include the reflecting structures, to an object, any change in length of the object will cause a change in the length of the reflecting structure which will be detected as a change in the characteristic wavelength. Furthermore, if these regions of the optical waveguide are placed in thermal contact with an object, any change in temperature will cause a change in the physical length of the reflecting structure which will be detected as a change in characteristic wavelength and the strain sensor of the present invention thus acts as an effective temperature sensor. It will be appreciated that in both measuring strain and temperature the strain sensor measures a change in the length of at least a part of the reflecting structure, that is it measures an internal strain of the sensor. In the context of the present invention the term strain sensor is intended to be construed broadly as a sensor which relies on a change in length and should not be restricted to a sensor which is for measuring strain in an object

to which it is attached.

Advantageously the reflecting structures which reflect at adjacent wavelengths are configured such that one structure reflects light at one characteristic wavelength and the structure adjacent in wavelength is selected to reflect light at two characteristic wavelengths. Preferably the reflecting structure which reflects light at two characteristic wavelengths is configured such that the two wavelengths are separated by at least the width of the reflection characteristic of the structure which reflects at the adjacent wavelength. Such an arrangement is particularly advantageous since at least one of the pair of characteristic wavelengths always remains resolvable and therefore discrimination between the reflecting structures is possible.

Most conveniently the optical waveguide comprises an optical fibre and preferably the or each reflecting structure comprises a grating structure, most preferably a Bragg grating, in which a change in the characteristic wavelength is in consequence of a change in the pitch of the grating. In a preferred implementation the optical fibre includes a photo refractive dopant, such as for example a silica optical fibre doped with germanium oxide, and the or each grating structure is optically written into the fibre core by, for example, exposing the fibre to ultra-violet (UV) holographic projection. In such a case the spacing of the fringes of the holographic projection determines the pitch and hence the characteristic wavelength of the grating and the intensity of the UV light determines the reflectivity at the characteristic wavelength.

According to a second aspect of the invention an apparatus for measuring strain

comprises a strain sensor described above; a light source operable to apply light to the waveguide of the sensor, said light having a wavelength range which covers at least the range of wavelengths over which the reflecting structures reflect and detector means for determining the change of characteristic wavelength at which each reflecting structure reflects light, said changes being indicative of a change in length of at least a part of the respective reflecting structure.

Preferably the detector means determines the changes in characteristic wavelength by measuring the wavelengths at which the sensor reflects light. Since the strain sensor only reflects light at various characteristic wavelengths, any light which is not reflected will pass along the optical waveguide substantially unattenuated. As a result, at the far end of the waveguide the changes in wavelength will appear as a change in attenuation of transmitted light. In an alternative arrangement the detector means measures light transmitted by the sensor and determines the changes by measuring the changes in wavelength at which light transmission is attenuated.

In a particularly preferred form of apparatus the detector means further comprises means for utilising the relative magnitude of the intensity of the reflected light or the relative magnitude of the intensity at which light transmission is attenuated to discriminate between reflecting structures which are adjacent in wavelength.

According to yet a further aspect of the invention a method of measuring strain comprises providing a strain sensor described above; applying light to the waveguide of the sensor, said light having a wavelength range which covers at least the range of wavelengths over

which the reflecting structure reflects light, and detecting any change in the characteristic wavelength at which the reflecting structures reflect light. Preferably the changes in characteristic wavelength are detected by measuring the wavelengths at which the sensor reflects light.

5

Alternatively the changes in characteristic wavelength can be detected by measuring the wavelengths at which the transmission of light through the sensor is attenuated.

Preferably the method further comprises detecting the relative magnitude of the intensity
10 of reflected light or the relative magnitude of the intensity at which transmitted light is attenuated to discriminate between reflecting structures which are adjacent in wavelength.

When it is desired to measure strain within an object the method further comprises
15 securing a part of the waveguide having at least a part of one of the reflecting structures to the object such that a change in the physical length of the object causes a change in the physical length of the reflecting structure. Alternatively, or in addition, when it is desired to measure the temperature of an object, the method further comprises placing a part of the waveguide having at least a part of one of the reflecting structures in thermal contact with the object such that a change in the temperature of the object causes a change in the
20 physical length of at least a part of the reflecting structure.

In order that the invention may be better understood a strain sensor and apparatus in accordance with the invention for measuring strain and/or temperature will now be described by way of example only with reference to the accompanying drawings in

which:

Figure 1 is a schematic of a strain and/or temperature sensing apparatus in accordance with the invention;

5

Figure 2(a) is a series of plots of measured reflectivity I versus wavelength for different applied strains for the apparatus of Figure 1;

10

Figure 2(b) is a plot of the measured wavelength shift $\Delta\lambda$ of the peak (x) of Figure 2(a) versus strain;

Figure 3(a) is a series of plots of measured reflectivity I versus wavelength for a further strain sensor for different applied strains; and

15

Figure 3(b) is a plot of the measured wavelength shift $\Delta\lambda$ for the two peaks (x,y) of Figure 3(a) versus strain.

20

Referring to Figure 1 a strain sensing apparatus comprises a broad band light source 2, a tunable filter 4, an optical fibre strain sensor 6, a directional coupler 8, two photodiodes 10 and 12 respectively, a mixer circuit 14 and a processor 16. The optical fibre strain sensor 6, which is a key aspect of the present invention and considered inventive in its own right, comprises a silica optical fibre which is doped germanium oxide. Spaced along the length of the optical fibre there are provided within the core of the optical fibre a plurality of Bragg diffraction gratings. Each grating is produced within the core of the

optical fibre by exposing the core of the fibre to ultra-violet (UV) light using holographic exposure, though other techniques such as a phase mask or point by point writing can be used. Germanium oxide is a photo refractive dopant which when exposed to UV light results in a permanent change of refractive index and hence a Bragg diffraction grating can be defined within the core by exposing the core to an appropriate pattern of UV light. Each grating structure within the fibre is selected to have a characteristic wavelength, denoted λ_1 to λ_{n+1} in Figure 1, which is determined by the pitch of the respective grating. The method of producing optical fibre gratings using holographic projection is known and is for example described in an article by one of the inventors in the GEC Journal of Technology Volume 15 Number 1, 1998, paragraph 2.3, which is hereby incorporated by way of reference thereto.

The gratings which reflect at adjacent wavelengths, for example λ_1 and λ_2 or λ_n and λ_{n+1} in Figure 1 are arranged to alternately have reflectivities of 50 and 95% respectively which will hereinafter be referred to as "low" and "high" reflectivity. Using the fabrication technique described this difference in reflectivity is achieved by altering the intensity of the UV light used to expose and so define the grating structure within the fibre. As will become apparent the absolute reflectivity of gratings which are adjacent in wavelength is not critical and the use of 50 and 95% are exemplary only. The important criterion is that the relative reflectivity of gratings which are adjacent in wavelength have sufficiently different reflectivities to enable discrimination between light reflected from the respective gratings. The optical fibre sensor 6 further comprises associated with each grating region mechanical securing means to enable the fibre to be mechanically secured to an object whose strain is to be measured. Such mechanical

securing means can comprise an encapsulating tube, flanges or mounting brackets made of metal, glass or a plastics material, to which the fibre is connected either by adhesive or by mechanical clamping.

- 5 The broad band light source 2, which conveniently comprises a light emitting diode or Erbium doped fibre amplifier, is operable to produce a continuous broad band light output over the wavelength range $1550 \text{ nm} \pm 30 \text{ nm}$. This continuous light output is applied to the wavelength selective filter 4, which can comprise for example an acousto-optic tuneable filter or a scanned Fabry-Perot filter, such that the filter produces an
- 10 optical output which is swept over the range of wavelengths of the broad band source 2. In an alternative arrangement the light source 2 and tuneable filter 4 can be replaced with a suitable optical source which is tuneable in the wavelength domain such as for example a tuneable laser diode. The swept light output is applied to the first input of the directional coupler 8 which splits the light such that half passes into and along the optical
- 15 fibre sensor 6 and the other half passes to the first photodiode 10. Light which is reflected by the Bragg gratings in the optical fibre sensor 6 travels back toward the directional coupler 8 where it is split such that half passes to the second photodiode 12 and the remaining half towards the wavelength selective filter 4. The light which is not reflected by the optical fibre sensor 6 passes along the length of the optical fibre and is
- 20 dissipated in a light dump 18 at the far end of the optical fibre.

The outputs from the respective photodiodes 10 and 12 are applied to the mixing circuit 14 such that the output represents the ratio of reflected light from the optical sensor 6 at a given wavelength relative to the intensity of light applied to the sensor at that

wavelength. As the tunable filter 4 scans over the wavelength bandwidth of the light source 2 the output from the mixer 14 represents the reflection spectrum of the sensor 6 which has been normalised relative to the light applied to it and this spectrum is detected by the processor 16 which preferably comprises a spectrum analyser. It is preferable, though not essential, to normalise the reflection spectrum as described since the source 2 is unlikely to produce a uniform light intensity output over its full spectral range.

Referring to Figure 2(a) there are shown the reflection intensity I profiles for a pair of “low” and “high” reflectivity gratings which are adjacent in wavelength versus wavelength for increasing amounts of applied tensile strain to the “low” reflectivity grating. These test data are for a sensor having an array of Bragg gratings having a 2nm spectral spacing and a typical grating bandwidth of $\approx 0.4\text{nm}$. The “high” (95%) reflectivity grating was kept strain free whilst the “low” (50%) reflectivity grating was strained in steps of $80\mu\epsilon$ up to $4000\mu\epsilon$, which corresponds to a 4nm change in wavelength.

Starting with the uppermost profile, which shows the sensor when no tensile strain is applied, it will be seen that the “low” reflectivity grating reflects light at a lower characteristic wavelength and the reflection peak is denoted “x” in the Figure. As tensile strain is applied to the “low” reflectivity grating, this causes an increase in the grating spacing, which causes the characteristic wavelength of the reflectivity peak x to increase and the peak moves toward and through the peak of the “high” reflectivity grating. For clarity, it should be noted that in this example no strain is applied to the “high” reflectivity grating and hence the characteristic wavelength of its reflectivity peak

remains constant.

Figure 2(b) is a plot of the wavelength shift $\Delta\lambda$ of the reflectivity peak x versus applied tensile strain. As will be seen from this Figure, the change in wavelength $\Delta\lambda$ is a linear
5 function of applied strain and includes a band over which strain cannot be measured; this is denoted by arrows "AA" in the Figure. In this band the reflection peaks from the "low" and "high" reflectivity gratings cannot be discriminated because they spectrally overlap, as illustrated in the middle profile of Figure 2(a). In spite of this band, whose width is approximately $500 \mu\epsilon$, it is still possible to double the number of gratings within
10 a given spectral range.

In the known systems the number of gratings (n) that can be incorporated into a single fibre is determined by $n \approx \Delta\lambda_{SR}/\Delta\lambda_{BG}$ where $\Delta\lambda_{SR}$ is the spectral range of the light source and $\Delta\lambda_{BG}$ is the spectral bandwidth of each fibre Bragg grating. The spectral bandwidth
15 $\Delta\lambda_{BG}$ is necessary to ensure that reflection peaks for adjacent gratings do not cross each other. In contrast to the known sensors, the sensor of the present invention additionally encodes the reflectivity of adjacent gratings which enables discrimination of the light reflected from the respective gratings. As a result in the spectral spacing necessary between adjacent gratings is approximately halved, though the strain sensing spectral
20 bandwidth for each grating is still $\Delta\lambda_{BG}$. The total number of gratings that can be incorporated within the fibre for a given spectral range is thus doubled.

As described above, there is a band AA in which the two gratings spectrally overlap and this band can be minimised by using narrow spectral response gratings. However, narrow

spectral response gratings will reflect less light, which will degrade the signal to noise ratio in the system. To minimise the effect of the overlapping region without the need to use ultra-narrow spectral response gratings, it is proposed in a further sensor according to the invention to replace the "low" reflectivity grating with one which is still of "low" reflectivity but reflects at two characteristic wavelengths. The spacing of the two characteristic wavelengths is selected to be at least as large as the bandwidth of the high reflectivity grating.

Referring to Figure 3, this shows for such a sensor (a) a series of plots of measured reflectivity I versus wavelength for different applied strains to the "low" reflectivity grating and (b) a plot of the measured wavelength shift $\Delta\lambda$ for the reflection peaks x,y of the low reflectivity grating versus applied strain. Referring to Figure 3(a) it will be seen that as the "low" reflectivity grating is subjected to strain the pair of reflectivity peaks (x,y) both shift at the same rate such that even when the spectral responses of the two gratings overlap at least one of the pair of peaks is always resolvable. Figure 3(b) shows the wavelength shift for both peaks (x,y) for the dual peak response as crosses and circles, respectively, versus applied strain. It will be seen that when information concerning both peaks of the dual peak response is considered the band AA over which strain cannot be measured is substantially reduced. The remaining small band is due to the relatively broad bandwidth of the high reflectivity grating. Further tests have shown that the gap is virtually eliminated if the spacing of the dual peaks is increased or if the bandwidth of the high reflectivity peak can be reduced.

It will be appreciated that the present invention is not restricted to the specific

embodiment described and that variations can be made which are within the scope of the invention. For example, in the apparatus described the intensity of the light reflected from the sensor is measured. In other embodiments it is envisaged to measure the light transmitted by the optical fibre, since the absorption loss in the fibre is negligible.

- 5 Consequently, the sum of transmitted light and reflected light is substantially unity and the change in characteristic wavelength of the Bragg gratings can be determined by measuring the change in wavelength at which the fibre attenuates transmitted light. It will be further appreciated that the invention is not limited to Bragg gratings, and other forms of reflecting structures can be used provided their characteristic wavelength is
- 10 affected by a change in the physical length of the structure. Although the sensor is conveniently formed as an optical fibre other forms of optical waveguide could be used though they are likely to be less convenient.

- The operation of the strain sensor has been described by way of example to strain sensing
- 15 within an object. It will be appreciated that the said strain sensor and apparatus can also be used to measure temperature, since a change in temperature of the grating will cause an expansion or contraction of the grating and so change the grating pitch. In such an application the optical fibre is placed in thermal contact, with the object rather than being secured to it.

CLAIMS

1. A strain sensor comprising: an optical waveguide (6) having a plurality of reflecting structures along its length, wherein each structure reflects light at a different characteristic wavelength (λ_1 to λ_{n+1}) which changes in dependence on a change of physical length of at least part of the reflecting structure; characterised in that the reflectivity of reflecting structures which reflect at characteristic wavelengths which are adjacent to each other (λ_1 and λ_2 , λ_n and λ_{n+1}) are configured to be different such that the intensity of light reflected from adjacent structures can be used to discriminate between them.
2. A strain sensor according to Claim 1 in which the reflecting structures which reflect at adjacent wavelengths are configured such that one structure reflects light at one characteristic wavelength and the structure adjacent in wavelength is selected to reflect light at two characteristic wavelengths.
3. A strain sensor according to Claim 2 in which the reflecting structure which reflects light at two wavelengths is configured such that the two characteristic wavelengths are separated by at least the width of the reflection characteristic of the structure which reflects at the adjacent wavelength.
4. A strain sensor according to any preceding claim in which the optical waveguide (6) comprises an optical fibre.


5. A strain sensor according to any preceding claim in which the or each reflecting structure comprises a grating structure and wherein the change in characteristic wavelength is in consequence of a change in the pitch of the grating.
6. A strain sensor according to Claim 5 in which the or each grating structure comprises a Bragg grating.
7. A strain sensor according to Claim 5 or 6 when dependent on Claim 4 in which the optical fibre (6) includes a photo refractive dopant and the or each grating structure is optically written into the fibre.
8. A strain sensor according to Claim 7 in which the optical fibre comprises silica doped with germanium oxide.
9. Apparatus for measuring strain; comprising a sensor according to any preceding claim, a light source (2, 4) operable to apply light to the waveguide of the sensor, said light having a wavelength range which covers at least the range of wavelengths over which the reflecting structures reflect and detector means (10-16) for determining the change of characteristic wavelength at which the reflecting structures reflect light, said changes being indicative of a change in length of at least a part of the respective reflecting structure.
10. Apparatus for measuring strain according to Claim 9 in which the detector means determines the change in characteristic wavelength by measuring the

wavelengths at which the sensor reflects light.

11. Apparatus for measuring strain according to Claim 9 in which the detector means measures light transmitted by the sensor and determines the change in characteristic wavelength by measuring the changes in wavelength at which light transmission is attenuated.
12. Apparatus according to any one of Claims 9 to 11 in which the detector means further comprises means for utilising the relative magnitude of the intensity of reflected light or the relative magnitude of the intensity at which light transmission is attenuated to discriminate between reflecting structures which are adjacent in wavelength.
13. A method of measuring strain comprising; providing a sensor according to any one of Claims 1 to 8, applying light to the waveguide of the sensor, said light having a wavelength range which covers at least the range of wavelengths over which the reflecting structure reflects light, and detecting any change in the characteristic wavelength at which the reflecting structures reflect light.
14. A method according to Claim 13 comprising detecting the change in characteristic wavelength by measuring the wavelengths at which the sensor reflects light.
15. A method according to Claim 13 comprising detecting the change in

characteristic wavelength by measuring the wavelengths at which the transmission of light through the sensor is attenuated.

16. A method according to Claim 14 or Claim 15 and further comprising detecting the relative magnitude of the intensity of reflected light or the relative magnitude of the intensity at which transmitted light is attenuated to discriminate between reflecting structures which are adjacent in wavelength.
17. A method according to any one of Claims 13 to 16 and further comprising sweeping the wavelength of the light applied to the sensor.
18. A method according to any one of Claims 13 to 17 in which, when it is desired to measure strain within an object, further comprises securing a part of the waveguide having at least a part of one of the reflecting structures to the object such that a change in the physical length of at least a part of the object causes a change in the physical length of at least a part of the reflecting structure.
19. A method according to any one of Claims 13 to 17 in which, when it is desired to measure the temperature of an object, further comprises placing a part of the waveguide having at least a part of one of the reflecting structures in thermal contact with the object such that a change in the temperature of the object causes a change in the physical length of at least a part of the reflecting structure.



2/3

Fig.2(a).





Fig.2(b).



3/3

Fig.3(a).





Fig.3(b).



Type a plus sign (+) inside this box → ☐

Approved for use through 8/30/98

PTO/SB/01 (6-95)

OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION <input type="checkbox"/> Declaration OR Submitted with Initial Filing <input checked="" type="checkbox"/> Declaration Submitted after Initial Filing	0010/PTO Rev. 8/95	U.S. Department of Commerce Patent and Trademark Office	Attorney Docket Number P/61761/PC
			First Named Inventor I. Bennion
			COMPLETE IF KNOWN
			Application Number 09/936,551
			Filing Date SEPTEMBER 14, 2001
			Group Art Unit
			Examiner Name

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

STRAIN SENSING

(Title of the Invention)

the specification of which

☐ is attached hereto
OR

☒ was filed on (MM/DD/YYYY)

March 17 2000

as United States Application Number or PCT International

S.N. 09/936,551

Application Number PCT/GB00/00994

and was amended on (MM/DD/YYYY)

(if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119 (a)-(d) or §385(b) of any foreign application(s) for patent or inventor's certificate, or §385 (a) of any PCT International application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
9906361.2	GB	March 19 1999	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
PCT/GB00/00994	INTERNATIONAL	March 17, 2000	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority sheet attached hereto:

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.
		<input type="checkbox"/>

Burden Hour Statement: This form is estimated to take .4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Type a plus sign (+) inside this box → +

DECLARATION

Page 2

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §385(c) of any PCT International application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.66 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application Number	PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT International application numbers are listed on a supplemental priority sheet attached hereto.

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Firm Name Customer Number or label
☒ OR
☒ List attorney(s) and/or agent(s) name and registration number below:

Name	Registration Number	Name	Registration Number
David B. Kirschstein, Esq.	17,244		
Alan Israel, Esq.	27,564		
Martin W. Schiffmiller, Esq.	30,421		

☐ Additional attorney(s) and/or agent(s) named on a supplemental sheet attached hereto.

Please direct all correspondence to: ☐ Customer Number OR ☒ Fill in correspondence address below

Name	KIRSCHSTEIN, OTTINGER, ISRAEL & SCHIFFMILLER, P.C.		
Address	489 Fifth Avenue		
City	New York	State	New York
Country	United States	Telephone	(212) 697-3750
		Fax	(212) 949-1690

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: ☐ A petition has been filed for this unsigned inventor

Given Name	Ian	Middle Initial		Family Name	BENNION	Suffix e.g. Jr.	
------------	-----	----------------	--	-------------	---------	-----------------	--

Inventor's Signature		Date	22/10/01
----------------------	---	------	----------

Residence: City	Northampton	Country	United Kingdom	Citizenship	British
-----------------	-------------	---------	----------------	-------------	---------

Post Office Address	25 Guilsborough Road, Ravensthorpe,
---------------------	-------------------------------------

Post Office Address	Northampton NN6 8EW, United Kingdom
---------------------	-------------------------------------

City	Northampton	State		Zip	NN6 8EW	Country	United Kingdom	Applicant Authority	
------	-------------	-------	--	-----	---------	---------	----------------	---------------------	--


☒ Additional inventors are being named on supplemental sheet(s) attached hereto

Type a plus sign (+) inside this box → ☐

DECLARATION					ADDITIONAL INVENTOR(S) Supplemental Sheet		
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor		
Given Name	John	Middle Initial		Family Name	WILLIAMS	Suffix e.g. Jr.	
Inventor's Signature	John Williams				Date	22/10/01	
Residence: City	Solihull	State		Country	United Kingdom	Citizenship	British
Post Office Address	15 Deanbrook Close, Shirley, Solihull						
Post Office Address	West Midlands B90 4XS, United Kingdom						
City	Solihull	State		Zip	B90 4XS	Country	United Kingdom
					Applicant Authority		
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor		
Given Name	Christopher	Middle Initial		Family Name	GROVES-KIRKBY	Suffix e.g. Jr.	
Inventor's Signature	C Groves-Kirkby				Date	10 Oct 2001	
Residence: City	Northampton	State		Country	United Kingdom	Citizenship	British
Post Office Address	19 West End, Bugbrooke, Northampton NN7 3PF,						
Post Office Address	United Kingdom						
City	Northampton	State		Zip	NN7 3PF	Country	United Kingdom
					Applicant Authority		
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor		
Given Name	Lin	Middle Initial		Family Name	ZHANG	Suffix e.g. Jr.	
Inventor's Signature	Lin Zhang				Date	22/10/01	
Residence: City	Birmingham	State		Country	United Kingdom	Citizenship	Chinese
Post Office Address	71 Solihull Lane, Hall Green						
Post Office Address	Birmingham B28 9LT, United Kingdom						
City	Birmingham	State		Zip	B28 9LT	Country	United Kingdom
					Applicant Authority		
Name of Additional Joint Inventor, if any:					<input type="checkbox"/> A petition has been filed for this unsigned inventor		
Given Name		Middle Initial		Family Name		Suffix e.g. Jr.	
Inventor's Signature					Date		
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		Zip		Country	
					Applicant Authority		

☐ Additional inventors are being named on supplemental sheet(s) attached hereto

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

Page 3 as part of preliminary amendment is
abstract.

☐ *Scanned copy is best available.*